

<b>AWG</b>	<b>Diameter [mm]</b>	<b>Area [mm<sup>2</sup>]</b>	<b>Resistance [Ohms / km]</b>	<b>Max Current [Amperes]</b>	<b>Max Frequency for 100% skin depth</b>
0000 (4/0)	11.684	107	0.16072	302	125 Hz
000 (3/0)	10.40384	85	0.202704	239	160 Hz
00 (2/0)	9.26592	67.4	0.255512	190	200 Hz
0 (1/0)	8.25246	53.5	0.322424	150	250 Hz
1	7.34822	42.4	0.406392	119	325 Hz
2	6.54304	33.6	0.512664	94	410 Hz
3	5.82676	26.7	0.64616	75	500 Hz
4	5.18922	21.2	0.81508	60	650 Hz
5	4.62026	16.8	1.027624	47	810 Hz
6	4.1148	13.3	1.295928	37	1100 Hz
7	3.66522	10.5	1.634096	30	1300 Hz
8	3.2639	8.37	2.060496	24	1650 Hz
9	2.90576	6.63	2.598088	19	2050 Hz
10	2.58826	5.26	3.276392	15	2600 Hz
11	2.30378	4.17	4.1328	12	3200 Hz
12	2.05232	3.31	5.20864	9.3	4150 Hz
13	1.8288	2.62	6.56984	7.4	5300 Hz
14	1.62814	2.08	8.282	5.9	6700 Hz
15	1.45034	1.65	10.44352	4.7	8250 Hz
16	1.29032	1.31	13.17248	3.7	11 kHz
17	1.15062	1.04	16.60992	2.9	13 kHz
18	1.02362	0.823	20.9428	2.3	17 kHz
19	0.91186	0.653	26.40728	1.8	21 kHz
20	0.8128	0.518	33.292	1.5	27 kHz
21	0.7239	0.41	41.984	1.2	33 kHz
22	0.64516	0.326	52.9392	0.92	42 kHz
23	0.57404	0.258	66.7808	0.729	53 kHz
24	0.51054	0.205	84.1976	0.577	68 kHz
25	0.45466	0.162	106.1736	0.457	85 kHz
26	0.40386	0.129	133.8568	0.361	107 kHz
27	0.36068	0.102	168.8216	0.288	130 kHz
28	0.32004	0.081	212.872	0.226	170 kHz
29	0.28702	0.0642	268.4024	0.182	210 kHz
30	0.254	0.0509	338.496	0.142	270 kHz
31	0.22606	0.0404	426.728	0.113	340 kHz
32	0.2032	0.032	538.248	0.091	430 kHz
33	0.18034	0.0254	678.632	0.072	540 kHz
34	0.16002	0.0201	855.752	0.056	690 kHz
35	0.14224	0.016	1079.12	0.044	870 kHz
36	0.127	0.0127	1360	0.035	1100 kHz
37	0.1143	0.01	1715	0.0289	1350 kHz
38	0.1016	0.00797	2163	0.0228	1750 kHz
39	0.0889	0.00632	2728	0.0175	2250 kHz
40	0.07874	0.00501	3440	0.0137	2900 kHz